

DigiPod™ Series

PUBLIC TRANSIT | DP-PT-F2TNX



WWW.TINNOX.COM.AU | © UFL TECHNOLOGY PTY LTD. All rights reserved.
All specifications and descriptions are subject to change without prior notice. Unauthorized reproduction is strictly prohibited.

TINNOX

SPECIFICATIONS

DP-PT-F2TNX

DISPLAY	LCD Brand	LG
	Brightness (w/o glass)	3500 nits
	Resolution	3840*2160
	Contrast Ratio	4000/1
	Light Lifetime (Typ.)	50,000 hours
	Viewing Angle	178°/ 178°
	Response Time (Typ.)	8ms
	No Blackening Defects	Up To 110°C
	Polarized Sunglasses Support	YES
	LCD Withstand Temperature	-30° +110°
	FUNCTIONS	Ambient Light Sensor
Temperature Controller		Yes
Lighting and leaking protectionion		Yes
Heat Dissipation Method		Air circulation system
MECHANICAL	Border Width	100/170mm
	Dimensions (W*H*D MM)	65": 1065*1825*274 / 75": 1130*2045*274 / 86": 1265*2290*274
	Material	Aluminum Alloy
	Painting Color	Black/Gray/Silver/Customize
	Thickness of Tempered Glass	6mm
	tempered Glass Transmittance	94%
	UV / IR Reflectivity	49%-53%
	Packaging method	Wooden box
	Weight	---
POWER	Electricity Supply	Internal
	Rated Voltage	110V-240V ~ 50/60Hz
	Power Consumption	800W
	Power Adapter	MeanWell power adapter / Chint leakage
ENVIRONMENTAL	Operating Temperature	-30°C to 60 °C (w/o Direct Sunlight)
	IP Rating	IP65
	Operational Hours	7/24 hrs
COMPUTER/OS	Optional/Open Slot	Made to Order/Install Own
CERTIFICATIONS	CE / FCC /RoHS	Yes